



HYDROFLOOR

Product Characteristics



Beskrivning

Round ground-recessed luminaire IP67 for outdoor installation, stainless steel AISI316 / AISI304 body and frame, tempered safety glass, moulded silicone gasket. With 1/3/ CREE LED. 24V DC remote driver or built-in LED driver.

- Completely made in stainless steel AISI 316 body
- Silicone rubber gasket
- Tempered safety glass.
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included

Ljusfördelning

ART	W	LM	IP	KELVIN	OPTION
201001	1	100	IP67	3000K/6000k	25°
201060	0,8	64	IP67	3000K	75°
201002	3	300	IP67	3000K/6000k	25°
201061	1,5	76	IP67	3000K	80°
201003	1	120	IP67	3000k/4000k	10°/30°/45°

LED DRIVER

ART	W	IP	TYPE
LPV-20-24	20	IP67	MEANWELL LED DRIVER 24V DC
LPV-35-24	35	IP67	MEANWELL LED DRIVER 24V DC
LPV-60-24	60	IP67	MEANWELL LED DRIVER 24V DC
LPV-100-24	100	IP67	MEANWELL LED DRIVER 24V DC



www.tupex.eu | info@tupex.eu